1. What are the specifications for the new Honda HS928 snowblower models? (see next page for features/options)

Specifications	HS928WA	HS928WAS	HS928TA	HS928TAS
Engine	Honda GX270	Honda GX270	Honda GX270	Honda GX270
Engine net power [kW (PS)/rpm]	8.5hp (6.3kW) @ 3600rpm	8.5hp (6.3kW) @ 3600rpm	8.5 hp (6.3kW) @ 3600rpm	8.5 hp (6.3kW) @ 3600rpm
Displacement	270cc / 16.5 cu in	270cc / 16.5 cu in	270cc / 16.5 cu in	270cc / 16.5 cu in
Starting System	Recoil	Electric/Recoil	Recoil	Electric/Recoil
Fuel capacity	1.58 gal / 5.98 L	1.58 gal/ 5.98 L	1.58 gal / 5.98 L	1.58 gal / 5.98 L
Drive Mechanism	Hydrostatic/Infinitely variable	Hydrostatic/Infinitely variable	Hydrostatic/Infinitely variable	Hydrostatic/Infinitely variable
Clutch type	Hydrostatic	Hydrostatic	Hydrostatic	Hydrostatic
Wheel / Track	Wheel	Wheel	Track	Track
Stages	2	2	2	2
Chute Turning Radius	210°	210°	210°	210°
Clearing Width	28 in / 710 mm	28 in / 710 mm	28 in / 710 mm	28 in / 710 mm
Clearing Height	20.1 in / 510 mm	20.1 in / 510 mm	20.1 in / 510 mm	20.1 in / 510 mm
Discharge Distance	49.5 ft / 15 m	49.5 ft / 15 m	49.5 ft / 15 m	49.5 ft / 15 m
Clearing Capacity (tons/hr)	50	50	50	50
Dimensions (L x W x H)	57.7 x 28.5 x 43.9 in 1465 x 723.9 x 1115 mm	57.7 x 28.5 x 43.9 in 1465 x 723.9 x 1115 mm	57.7 x 28.5 x 44.3 in 1465 x 723.9 x 1125 mm	57.7 x 28.5 x 44.3 in 1465 x 723.9 x 1125 mm
Dry Weight	209 lbs / 94.8 kg	220 lbs / 99.7 kg	243 lbs / 110.2 kg	254 lbs / 115.2 kg
Warranty	3 year limited	3 year limited	3 year limited	3 year limited

2. What are the specifications for the new Honda HS1332 snowblower models?

Specifications	HS1332TA	HS1332TAS
Engine	Honda GX390	Honda GX390
Engine net power [kW (PS)/rpm]	11.7hp (8.7kW) @3600 rpm	11.7hp (8.7kW) @3600 rpm
Displacement	389 cc / 23.73 cu in	389 cc / 23.73 cu in
Starting System	Recoil	Electric only
Fuel capacity	1.51 gal / 5.71 L	1.51 gal / 5.71 L
Drive Mechanism	Hydrostatic/Infinitely variable	Hydrostatic/Infinitely variable
Clutch type	Hydrostatic	Hydrostatic
Wheel / Track	Track	Track
Stages	2	2
Chute Turning Radius	210°	210°
Clearing Width	32 in / 812.8 mm	32 in / 812.8 mm
Clearing Height	20.1 in / 510.54 mm	20.1 in / 510.54 mm
Discharge Distance	56.1 ft / 17 m	56.1 ft / 17 m
Clearing Capacity (tons/hour)	65	65
Dimensions (L x W x H)	57.7 x 32.5 x 44.3 in 1465 x 825.5 x 1125.2 mm	57.7 x 32.5 x 46.1 in 1465 x 825.5 x 1170.9 mm
Dry Weight	265 lbs / 120.20 kg	276 lbs / 125.19 kg
Warranty	3 year limited	3 year limited

HS928 Features/Options:

Honda overhead valve engine
Automatic decompression for easy starting
Self-propelled
Adjustable snow deflection
Interconnected drive/auger control
Convenient control levers
Metal auger housing
Auger height adjustment pedal
(TA and TAS models only)
120 volt electric starter *(WA and TA models only)*
Fuel level gauge *(WAS and TAS models only)*
Light kit
Drift breaker kit

HS1332 Features/Options:

Honda overhead valve engine
Automatic decompression for easy starting
Self-propelled
Adjustable snow deflection
Interconnected drive/auger control
Convenient control levers
Metal auger housing
Auger height adjustment pedal
120 volt electric starter *(TAS model only)*
Fuel level gauge
Light kit
Drift breaker kit *(optional on the TA and TAS models)*